

JOLUKA

Joluka Plastic Spacer Datasheet

Plastic Spacer Technical Datasheet

Product Description

The Joluka Plastic Spacers are used for horizontal reinforcements such as suspended slabs, beams, etc and offer good stability. The concave seat accommodates steel diameters of 6-40mm. The design of the Joluka Plastic Spacer does not obstruct concrete flow. Use approximately 2-4m².

Characteristics/Advantages

- ☒ High strength up to 4 KN
- ☒ Manufactured from Recycled High-Density Polypropylene
- ☒ Designed with recess to support Reinforcing
- ☒ Designed to allow maximum flow of concrete
- ☒ Designed with hooks to secure Binding Wire
- ☒ Suitable for Reinforcing from 6 - 40mm
- ☒ Larger Covers (60 - 100mm) are made with a wider base
- ☒ Quick and Easy to Install

Typical Uses

- ☒ Reinforcement
- ☒ All types of applications on site or in the pre-cast concrete yard
- ☒ Suitable for most reinforcing applications



PRODUCT DATA

Colour :	Grey
Packaging:	Bags
Storage Conditions:	Store away from direct sunlight, will become brittle.
Composition:	Concrete

Joluka (Pty) Ltd
349 Roan Crescent
Corporate Park North
Midrand

Telephone: (011) 314 0795
Fax: (011) 314 5245
Website: www.joluka.co.za
Email: sales@joluka.co.za