

JOLUKA

SYSTEMS FOR REINFORCED CONCRETE AND BRICK STRUCTURES

90% SHADE NETTING 240 GSM

DATASHEET

Product Description

Joluka Shade Netting provides 90% Shade Factor with a weight per area of 240 GSM, perfect for long lasting protection of your most valuable assets. Manufactured in HDPE (High-Density Polyethylene) Mono + Tape Filament with a special heat setting process applied, which pre-stresses the shade cloth so that it will never sag for years to come. This product meets the standard specification.

General Information:

Material:	380 Denier Monofilament
Material Type:	100% High Density Polyethylene
Fabric:	Knitted Monofilament
UV Warranty:	10 Years
Application:	Car Ports, Shade Ports, Playgrounds, Parking Lots and Sports Grounds.
Colours:	Black, Charcoal, Silver, Forest Green, Royal Blue

Product Specifications:

	Green	Charcoal	Black
Bursting Strength	1329.5 N	1234.5 N	1332.3 N
Tensile Strength	(MD) 841.5 N (CD) 1120.2 N	(MD) 964.4 N (CD) 1110.4 N	(MD) 893.0 N (CD) 1161.7 N
Elongation	(MD) 75.1% (CD) 46.0%	(MD) 84.7% (CD) 49.3%	(MD) 68.1% (CD) 65.9%
Tearing Strength	(MD) 158.0 N (CD) 147.5 N	(MD) 148.5 N (CD) 149.0 N	(MD) 105.9 N (CD) 136.3 N
Light Blocking	90.5 %	95.87 %	89.68 %
Ultra Violet Blocking			
UV-R	94.4 %	95.6 %	95.0 %
UV-A	94.4 %	95.6 %	95.0 %
UV-B	94.4 %	95.6 %	94.9 %

* MD - Machine Direction
CD - Cross Direction

Joluka Pty (Ltd). 349 Roan Crescent, Corporate Park North, Midrand, Johannesburg 011 314 0795, web: www.joluka.co.za, e-mail: sales@joluka.co.za The information contained herein is offered without charge for use by technically qualified personnel at their discretion and risk. All statements, technical information and recommendations contained herein are based on tests and data which we believe to be reliable, but the accuracy or completeness thereof is not guaranteed and no warranty of any kind is made with respect thereto.